

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 2

Amendments to the claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Claims 1, 7, 11, and 13-14 are amended.

Claims 9 and 10 are canceled.

Listing of Claims:

1. (Currently Amended) A suspension system for a vehicle, the suspension system comprising:

right and left suspension arms, each suspension arm coupled to a frame of the vehicle and a wheel of the vehicle, the suspension arms being coupled to the frame so that the suspension arms are capable of independent movement;

right and left linking mechanisms, each linking mechanism being coupled to the respective suspension arm;

a shock absorber with two ends, one end of the shock absorber being coupled via the respective linking mechanism to the right arm and the other end of the shock absorber being coupled via the respective linking mechanism to the left arm; [[and]]

a swinging mechanism, the swinging mechanism being coupled to the right and left linking mechanisms and to the frame of the vehicle, the swinging mechanism being configured to provide a damping force to restrict rotation of frame of the vehicle; and

a connecting member being coupled to the right and left linking mechanisms.

wherein the connecting member is attached to the frame via the swinging mechanism.

2. (Original) The suspension system according to claim 1, wherein the linking mechanisms comprise:

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 3

- right and left linking arms, respectively; and
- right and left bell cranks, respectively, wherein each bell crank is coupled to an end of the shock absorber, the respective linking arm, and to the swinging mechanism.
3. (Original) The suspension system according to claim 2, wherein each bell crank is coupled to the swinging mechanism via a connecting member, the connecting member being pivotably coupled to the frame of the vehicle.
4. (Original) The suspension system according to claim 3, wherein the swinging mechanism is a Neidhart damper.
5. (Original) The suspension system according to claim 3, wherein the linking arms are arc-shaped.
6. (Original) The suspension system according to claim 3, wherein the suspension arms are A-type arms.
7. (Currently Amended) A three-wheel vehicle with a suspension system, the suspension system comprising:
- a spindle extending in a longitudinal direction of the vehicle and attached to a body frame, the body frame being pivotably attached to the spindle;
 - right and left suspension arms independently coupled to the spindle so that they are capable of pivoting about the spindle;
 - right and left rear wheels attached to a right and left side of the body frame via the respective suspension arms; [[and]]
 - a swinging mechanism coupled to the body frame, the swinging mechanism

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 4

configured to restrict lateral rotation of the body frame and provided between the suspension arms and the body frame, and
a shock absorber with two ends, each end of the shock absorber being coupled to a side of one of the suspension arms,
wherein the shock absorber is coupled to the suspension arms via a linking mechanism, the linking mechanism comprising:
right and left linking arms; and
right and left bell cranks, each bell crank being coupled to an end of the shock absorber, the respective linking arm, and to the swinging mechanism.

8. (Original) The vehicle according to claim 7, wherein the suspension arms are A-type arms.

9-10. (Canceled)

11. (Currently Amended) The vehicle according to claim [[10]] 7, wherein each bell crank is coupled to the swinging mechanism via a connecting member, the connecting member being pivotably coupled to the frame of the vehicle.

12. (Original) The vehicle according to claim 7, wherein the swinging mechanism is a Neidhart damper.

13. (Currently Amended) The vehicle according to claim [[10]] 7, wherein the linking arms are arc-shaped.

14. (Currently Amended) A three-wheel vehicle with a suspension system, the

Application No. 10/764404
Reply to Office action of 6/23/2005
Page 5

suspension system comprising:

spindle means extending in a longitudinal direction of the vehicle for allowing rotation about an axis defined by the spindle means, the spindle means being attached to a body frame with the body frame being capable of pivoting about the spindle means;

right and left suspension means for coupling right and left rear wheels to a right and left side of the body frame, the suspension means being pivotably coupled to the spindle; and

swinging means for restricting lateral swing of the body frame, the swinging means being coupled to the body frame and provided between the suspension means and the body frame,

wherein the swinging means includes:

a front swinging shaft,

a rear swinging shaft,

a left suspension arm, and

a rear suspension arm,

wherein the left and right suspension arms are independently attached to the front swinging shaft and the rear swinging shaft, and

the left and right suspension arms are each pivotally coupled to an axis of the left and right rear wheels, respectively.